

32 AMP
EC 350

EstrichBoy EC 350 BS

The powerful 32-amp
compressed air conveyor



Illustration shows special paint

For earth-moist screed

- Cement screed
- Calcium sulphate screed (anhydrite)
- Magnesia screed
- Vibration-laid tiling



A trick up your sleeve for working in green zones

The EstrichBoy EC 350 BS is quieter, with zero emissions and no diesel costs. With a 32-amp connection, it can be used on any construction site and the costs for its electricity supply can usually be charged at a flat rate through the construction site levy.

- Particularly suitable for noise-sensitive areas
- Optional innovative 16-amp additional drive for conveying at a width of up to 100 m and a height of up to 50 m*
- High delivery rates of 3 m³/h or 3.5 m³/h with the additional drive shorten working times and therefore reduce labour costs
- Reliable, robust and easy to use
- Weight of 1900 kg allows it to be towed by a range of towing machines



BRINKMANN



Optional drive for an additional performance boost



Standard 32 A socket and 16 A socket with optional additional drive



Storage box for essential tools



Robust keypad with a coloured LED display

Working lights

All the benefits at a glance

- **Overload protection ensures interruption-free work**
- **Can be reduced to 25 amps if required for the construction site**
- **Intelligent delivery air control leads to shorter delivery times**
- **Premium service with original parts from certified workshops**
- **Shock-proof socket for lights, etc. is available**

Equipment

	Series	Optional
Car coupling with height-adjustment	■	
Central grease lubrication	■	
Hood painting in orange	■	
Light holder (12 V)	■	
Shock-proof socket	■	
Additional drive (5.5 kW)		■
Blockage alert		■
Conversion to 100 km/h		■
Customer labelling		■
Electric cable 16 A 30 m		■
Electric cable 32 A 30 m		■
High-pressure cleaner		■
Hoop guard set		■
Lifting eye		■
Light holder (24 V)		■
Mixing time adjustment		■
Power distributor 63 A		■
Protective plate for feeder		■
Special paint for hood in RAL		■
Support feet		■
Tool box (incl. hoop guard set)		■
Truck coupling		■
Wear plate on the dome		■
Wear plates (Hardox 6 mm)		■
Wear plates (Hardox 8 mm)		■
Wear plates front end/mid		■
Wear plates plastic		■
Working lights		■

Technical data

	EstrichBoy EC 350 BS 32 A	EstrichBoy EC 350 BS 32 A with 16A additional drive
Mixer drum	260 l, 200 l useful cap.	260 l, 200 l useful capacity
Output (theor.)*	3 m³/h	3.5 m³/h
Delivery pressure*	8 bar	8 bar
Delivery range*	80 m wide, 40 m high	100 m wide, 50 m high
Air reservoir	400 l	400 l
Compressor	2.3 m³/min	2.7 m³/min
Drive motor	15 kW	20.5 kW
Weight	1900 kg	1900 kg
L x W x H	4800 x 1580 x 2450 mm	4800 x 1580 x 2450 mm
Filling height	400 mm	400 mm
Chassis	up to 80 km/h permissible	
Special feature	hydraulic feeder and scraper	

*The data is based on empirical values and depends on the materials used

BRINKMANN

A brand of the Putzmeister Group

Max-Eyth-Straße 10 · 72631 Aichtal / Germany

Tel. +49 7127 599-0 · Fax +49 7127 599-743

brinkmann@estrichboy.de · www.estrichboy.de



BRINKMANN