



Rendering machine

PH9B-S



New model rendering machine PH9B-S with fixed mixer and discharge by lateral doors. New design and technical optimization of a recognized solution since many years for its simplicity, its efficiency and its robustness.



- Machine fully designed using reliable and known technical solutions
- Patented dust extraction system, very efficient as it is directly connected to the the mixer
- Fixed mixer offering discharge by twin lateral doors. Simple, effortless and optimal tightness
- Simple and user-friendly control panel and water meter system
- Optimal balance on the drawbar for better manoeuvrability on jobsite
- Less maintenance time with the main components freely and easily accessible
- Back side completely redesigned avec LED lights and bumper for side and rear protections
- Low operating cost

Rendering machine

PH9B-S



USER SAFETY

- Dust extraction system = 95% less dust
- Low noise emission
- Very good balance, drive axle without brake

USER COMFORT

- Machine compact, easy to handle with low loading height
- Ergonomic, full, waterproof and centralized control panel
- Adjustable spray flow rate
- Simple water meter system with digital display
- Pumping and mixing simultaneously
- High pressure cleaner (in option). Can be used simultaneously when pumping.

MANPOWER GAIN

- Complete equipment to ensure perfect material mixing and pumping
- Twin lateral discharge doors
- Low costs of ownership. Robust machine with reliable components
- Handles on the mixer grid, easy to open and better manoeuvrability
- Two rearming buttons grid on each side of the machine

CREATIVE TECHNOLOGY

- Optimized compressor system for optimal reliability
- New mortar hoses with larger internal diameter
- Automatic compressor belt tension
- Compressor venting = full load only while spraying
- Engine + compressor on silent blocks = no vibration
- Nouveau control panel with service warning
- New plug and play diesel filtration



DISTRIBUTED BY

TECHNICAL SPECIFICATIONS	PH9B-S
Theoretical flow rate *	60 L/min max. (with 2L61) • 100 L/min max. (with 1,5L63)
Maximum grain size	6 mm
Discharge distance **	L 100 m / H 40 m
Engine	Liquid-cooled Kubota engine 3-cyl 14,5 kW
Mixer	Fixed tank with discharge doors Capacity 180 L Loading height 1,10 m
Pumping hopper capacity	200 L
Worm pump	2L61 or 1,5L63
Pumping	Pneumatic control from the spraying nozzle
Twin cylinder compressor	400 L/min
Safety	Automatic on opening of the mixer and feeder hopper grids
Sound level at work place	<85 dB
Sound power	< 99 LWA
Axle	Unbrake, road approval
Level adjustment	Hand-cranked support stilt
Total weight (all options)	< 750 kg
Dimensions (road version)	3400 x 1450 x 1200 mm (L x l x h)

* The delivery rate is theoretical and depends on the pumping material properties and jobsite configuration.
** No-cumulative, maximum distances and depend on pumping material properties.



PL2M • Parc d'activités - 26 Avenue des Mondaults - 33270 Floirac
www.lancy.com • info@lancy.com

